



**NOTES**

- 1 CONCRETE GRADE N32 MINIMUM TO AS1379 & AS3600
- 2 PIT TO BE REINFORCED WITH Y12 @ 200CRS EACH WAY OR SL82 MESH, & SINGLE Y12 "U" BAR IN GRATE SURROUND
- 3 FOR SAG GULLY, POSITION GRATE CENTRALLY IN LINTEL
- 4 BRAND NAMES, CATALOGUE NUMBERS WHERE SHOWN ARE INDICATIVE OF MINIMUM ACCEPTABLE STANDARDS ONLY. HOWEVER COUNCILS PREFERENCE IS TO THOSE STATED AND ANY ALTERNATIVE SHALL BE SUBJECT TO APPROVAL BY THE DIRECTOR OF ENGINEERING SERVICES.
- 5 GRATE LOAD CAPACITY TO BE CLASS 'C' OR GREATER IN ACCORDANCE WITH AS3996-1992
- 6 GRATE PATTERN TO PREVENT BICYCLE TYRE CAPTURE
- 7 PIT DEPTH SHALL NOT EXCEED 3500

SCALE 1:10 0 0.1 0.2 0.4 0.6 0.8 1.0 m

<p><b>TWEED SHIRE COUNCIL</b> PLANNING AND DESIGN UNIT</p> <p>COUNCIL OFFICES TUMBULGUM ROAD, MURWILLUMBAH, NEW SOUTH WALES, 2484</p> <p>PHONE MURWILLUMBAH 02 66720400 FAX MURWILLUMBAH 02 66727513 EMAIL imunro@tweed.nsw.gov.au</p>		<p>DESIGN ENGINEER (SIGNED) <i>[Signature]</i> DATE 5.2004</p> <p>PLANNING &amp; DESIGN MGR. <i>[Signature]</i> DATE 5.2004</p> <p>DESIGNED R.A.E. 2.2004 DESIGN NO.</p> <p>DRAWN R.A.E. 2.2004 SURVEY NO.</p> <p>CHECKED W.B. 2.2004 REDUCTION RATIO</p> <p>HORIZONTAL DATUM</p> <p>VERTICAL DATUM</p>	<p>PROJECT:</p> <p><b>STORMWATER STANDARDS</b></p> <p>PLAN TITLE:</p> <p><b>STANDARD GULLY PIT - ROLL TOP KERB</b></p>	<p>DRAWING NUMBER:</p> <p><b>S.D.103</b></p> <p>SHEET 1 OF 1 SHEETS</p> <p>ISSUE A B</p>
<p>B DRAWINGS ADOPTED FOR ISSUE TO PUBLIC R.A.E. 5.2004</p> <p>A RE-ISSUED R.A.E. 4.2004</p> <p>ISSUE AMENDMENT DETAILS INITIALS DATE</p>	<p>0 10 20 30 40 50 100 150 200 250</p> <p>NOTE: FULL SIZE ON ORIGINAL. ACAD FILE No G:\TSC STANDARD DRAWINGS\S.D.DRAWINGS\100STORMWATER\S.D.103.DWG</p>			